



Professional Stacked Washers and Dryers

SPS10, SPSC10

SDS10, SDSC10





EASY OPERATION

FEATURES STACK UNITS

- Totally freestanding:can be instaled on any floor and any level
- Reduced floor space
- OPL or Coin operated versionsTop, front and side panels standard available in anthracite greyDoor opens 180° for easy loading and
 - unloading
 - LED indication of the status of the program
 - Time remaining countdown

FEATURES WASHER EXTRACTORS

- Stainless steel outer and inner drum
- Industry-leading 440 G-Force extraction removes more moisture, minimizing drying times and utility costs
- Suspension with new out-of-balance logic
- Soap box with four compartments
- Standard with drain pump, drain valve optionally available • Electrical heating or boiler-fed
- 6 wash programs
- Possibility of programming cycle modifier options » Added prewash » Extra wash time » Extra rinse

FEATURES DRYERS

- Galvanized steel cylinder
- Oversized lint filter located in front for easy cleaning
- Powerful exhaust blower assures short drying times and low operating costs
- Electrical or gas heating
- 4 drying programs LED indication of the status of the program






| ТҮРЕ | | WASHER | | |
|----------------------|-----|--------------------|--|--|
| CAPACITY | kg | 10 | | |
| DRUM VOLUME | 1 | 96,8 | | |
| MOTOR | | | | |
| Frequency controlled | kW | 0,67 | | |
| EXTRACTION SPEED | rpm | 1200 | | |
| G-FACTOR | | 440 | | |
| ELECTRICAL | | 1x220-240V 50/60Hz | | |
| CONNECTION | | 3x220-240V 50Hz | | |
| | | 3×380-415V+N 50 Hz | | |
| ELECTRICAL HEATING | kW | 4,8 | | |
| DRAIN | | | | |
| Pump | | standard | | |
| Drain valve | | available | | |

| ТҮРЕ | | DRYER |
|-------------|----|--------------------|
| CAPACITY | kg | 10 |
| DRUM VOLUME | | 198 |
| ELECTRICAL | | 1×220-240V 50/60Hz |
| CONNECTION | | 3×220-240V 50Hz |
| | | 3×380-415V+N 50 Hz |
| ELECTRICAL | kW | 5,2 (230V) |
| HEATING | | 5,3 (400V) |
| GAS HEATING | kW | 7,3 |
| MOTOR POWER | kW | 0,25 |


| ТҮРЕ | | SPS10 | SPSC10 | SDS10 | SDSC10 |
|---------------------|----------------|--------------|--------|----------------------|--------|
| MODEL | | washer/dryer | | dryer/dryer | |
| USE | | OPL | COIN | OPL | COIN |
| DIMENSIONS H×W×D | mm | 1986×683×704 | | 1986x683x737 | |
| TRANSPORT DATA | kW | | | | |
| Gross weight | kg | 193 | | 127 (el.) /132 (gas) | |
| Net weight | kg | 177 | | 120 (el.) /125 (gas) | |
| Volume (packed) | | | | | |
| Cardboard packing | m ³ | 1,25 | | 1,30 | |
| Dimensions (packed) | | | | | |
| H×W×D | mm | 2032×737×832 | | 2032×737×865 | |

Side View

Back










SPS10/ SPSC10

Side View





Front View



SDS10/ SDSC10

ISO 9001 ISO 14001 BUREAU VERITAS Certifi<u>cation</u> ((



Primus preserves the right to change the machines and the specification in this leaflet at any time, without prior notice. Details and photographs are only for information and never binding.

www.primuslaundry.com